

# NEW Conext XW+ NA inverter/charger

## One solution for global power needs

Conext™ XW+ is an adaptable single-phase and three-phase inverter/charger system with grid-tie functionality and dual AC power inputs. Available solar charge controllers, monitoring, and automated generator control modules enable further adaptability. From a single Conext XW+ unit to clusters up to 102 kW, the Conext XW+ is a scalable system that allows for the integration of solar capacity as required. Adaptable and scalable, the Schneider Electric™ Conext XW+ system is the one solution for grid-interactive and off-grid, residential and commercial, solar and backup power applications.

### Why choose Conext XW+ NA?



#### True bankability

- Warranty from a trusted partner with over 177 years of experience
- World leader in industrial power drives, UPS and electrical distribution
- Strong service infrastructure worldwide to support your global needs



#### Higher return on investment

- Excellent load starting with high 30-minute and 5-second power
- Performs in hot environments up to 70°C
- Intelligent functionality enables solar prioritization, load shifting, peak shaving, and assists small generators with heavy loads
- Backup power with grid-tie functionality converts external DC power to AC power for export to the utility grid



#### Flexible

- Single or three phase systems from 7.0 kW to 102 kW
- Supports DC coupled and AC coupled off-grid and grid-tie architectures
- Supports charging of Lithium Ion battery packs



#### Easy to service

- Field serviceable with replacement boards and spare parts
- Monitor, troubleshoot or upgrade firmware with Conext ComBox



#### Designed for reliability

- Extensive quality and reliability testing
- Highly Accelerated Life Testing (HALT)
- Globally proven and recognized field performance



#### Easy to install

- System configures quickly into compact wall-mounted system
- Integrates both grid and generator power with dual AC inputs
- Balance of system components integrates battery bank, solar charge controllers and generators
- Commission the entire system with PC software tool and Conext ComBox



### Product applications



Residential grid-tie solar with backup power



Self-consumption




off-grid solar



Backup power



Community electrification



Device short name	XW+ 5548 NA	XW+ 6848 NA
<b>Inverter AC output</b>		
Output power (continuous) at 25°C	5500 W	6800 W
Overload 30 min / 60 sec at 25°C	7000 W / 9500 W	8500 W / 12000 W
Output power (continuous) at 40°C	4500 W	6000 W
Maximum output current 60 seconds (rms)	82 A (120 V); 41 A (240 V)	102 A (120 V); 52 A (240 V)
Output frequency (selectable)	50 / 60 Hz	50 / 60 Hz
Output voltage	L-N: 120 V +/- 3%; L-L: 240 V +/- 3%	L-N: 120 V +/- 3%; L-L: 240 V +/- 3%
Total harmonic distortion (THD) at rated power	< 5%	< 5%
Idle consumption search mode	< 8 W	< 8 W
Input DC voltage range	42 to 60 V (48 V Nominal)	42 to 60 V (48 V Nominal)
Maximum input DC current	150 A	180 A
<b>Charger DC output</b>		
Maximum output charge current	110 A	140 A
Output voltage range	40 - 64 V (48 V Nominal)	40 - 64 V (48 V Nominal)
Charge control	Three stage, two stage, boost, custom	Three stage, two stage, boost, custom
Charge temperature compensation	Battery temperature sensor included	Battery temperature sensor included
Power factor corrected charging	0.98	0.98
Compatible battery types	Flooded (default), Gel, AGM, LiON, custom*	Flooded (default), Gel, AGM, LiON, custom*
Batter bank range (scaled to PV array size)	440 - 10000 Ah	440 - 10000 Ah
<b>AC input</b>		
AC 1 (grid) input current (selectable limit)	3 - 60 A (60 A default)	3 - 60 A (60 A default)
AC 2 (generator) input current (selectable limit)	3 - 60 A (60 A default)	3 - 60 A (60 A default)
Automatic transfer relay rating / typical transfer time	60 A / 8 ms	60 A / 8 ms
AC input voltage limits (bypass/charge mode)	L-N: 78 - 140 V (120 V nominal) L-L: 160 - 270 V (240 V nominal)	L-N: 78 - 140 V (120 V nominal) L-L: 160 - 270 V (240 V nominal)
AC input frequency range (bypass/charge mode)	55 - 65 Hz (default); 52 - 68 Hz (allowable)	55 - 65 Hz (default); 52 - 68 Hz (allowable)
<b>AC grid-tie output</b>		
Grid sell current range on AC1(selectable limit)	0 to 40 A (120 V) / 0 to 20 A (240 V)	0 to 48 A (120 V) / 0 to 27 A (240 V)
Grid sell voltage range on AC1 (auto adjusts entering sell mode)	L-N:105.5 to 132 +/- 1.5 V L-L: 211 to 264 +/- 3.0 V	L-N:105.5 to 132 +/- 1.5 V L-L: 211 to 264 +/- 3.0 V
Grid sell frequency range on AC1 (auto adjust entering sell mode)	59.4 to 60.4 +/- 0.05 Hz	59.4 to 60.4 +/- 0.05 Hz
<b>Efficiency</b>		
Peak	95.7%	95.7%
CEC weighted efficiency	93.0%	92.5%
<b>General specifications</b>		
Part number	865-5548-01	865-6848-01
Product / shipping weight	53.5 kg (118.0 lb) / 75.0 kg (165.0 lb)	55.2 kg (121.7 lb) / 76.7 kg (169.0 lb)
Product dimensions (H x W x D)	58 x 41 x 23 cm (23 x 16 x 9 in)	58 x 41 x 23 cm (23 x 16 x 9 in)
Shipping dimensions (H x W x D)	71.1 x 57.2 x 39.4 cm (28.0 x 22.5 x 15.5 in)	71.1 x 57.2 x 39.4 cm (28.0 x 22.5 x 15.5 in)
IP degree of protection	NEMA Type 1 Indoor	
Operating air temperature range	-25°C to 70°C (-13°F to 158°F) (power derated above 25°C (77°F))	
Warranty (Depending on the country of installation)	2 or 5 years	2 or 5 years
<b>Features</b>		
System monitoring and network communications	Available	
Intelligent features	Grid sell, peak load shave, generator support, prioritized consumption of battery or external DC energy	
Auxiliary port	0 to 12 V, maximum 250 mA DC output, selectable triggers	
Off-grid AC coupling	Frequency control	
Multi-unit operation	Single and split phase: up to four units in parallel, three phase: up to 12 units in multi-cluster configuration with external AC contractor	
<b>Regulatory approval</b>		
Safety	UL1741, CSA 107.1	
EMC directive	FCC and Industry Canada Class B	
Interconnect	IEEE 1547 and CSA 107.1	

Specifications are subject to change without notice.

**Conext XW+ works with the following Schneider Electric products**



**XW+ Power Distribution Panel**  
Product no. 865-1015-01



**Conext System Control Panel**  
Product no. 865-1050-1



**Conext Automatic Generator Start**  
Product no. 865-1060-01



**MPPT 60 150 solar charge controller**  
Product no. 865-1030-1



**MPPT 80 600 solar charge controller**  
Product no. 865-1032



**Conext Combox communication device**  
Product no. 865-1058



**Conext Battery Monitor**  
Product no. 865-1080-01

**XW Configuration Tool**  
Product no. 865-1155